

## 安全資料表

## 危害物料資料

1.1 物料名稱 :	Oxygen (氧氣)									
1.3 用途	風煤									
2. 危害成份										
2.1 危害分類及標籤 <sup>:</sup>	HARMFUL 行吉	TOXIC			RROSIVE 6触性	FLAMMABLE 品概	IRRITANT 刺激性	EXPLOSIVE 場作性	OXIDIZING	
	有害	1	有毒	腐	蝕性	易燃	刺激性	爆炸性	助燃	
	( )	(	)	(	)	( )	( )	( )	( ✓ )	
2.2 酸鹼值(pH) :	無資料 2.3 曝露限制(OEL) : 無資料									
2.4 致癌物質 :	無資料				2.5 其他危害 :					
2.5 潛在危害 :	助燃性高,遇火會引致爆炸的可能									
3. 火警和爆炸資料										
3.1 燃燒物成份比例 <sup>:</sup>	無資料 3.2 沸點(			弗點(°	°C): -118		3.3 溶	3.3 溶點(℃) : -219		
3.4 閃點(℉)	不適用 3.5 比重			比重	:1.1		3.6 氣	3.6 氣壓力 : 無資料		
3.7 爆炸極限(濃度)	無資料 3.8 溶解			容解度	<b>支</b> : 🗉	「溶於水	3.9 氣	味 : ※	沒有	
3.10 滅火設備	水劑、二氧化碳、化學乾粉沬之滅火筒									
4. 急救處理										
4.1 眼睛接觸 <sup>:</sup>	不適用									
4.2 皮膚接觸	不適用									
4.3 吸入	不適用									
5. 個人防護裝備										
□ 橡膠手套	[	☑ 護眼罩						口罩		
6. 處理及使用應知事項										
6.1 儲存注意事項:		<ul><li>儲存於攝氏50度以下陰凉、通風位置</li><li>遠離熱源、火種</li><li>必需垂直擺放,並加以穩固</li><li>避免受陽光直接照射</li></ul>								
6.2 意外洩漏處理的方法: 無資料										
7. 其他資料										
- 存放位置嚴禁吸煙										



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## SECTION 1: Identification of the substance or mixture and of the company

### 1.1 Product Identifier

Product name : Oxygen, compressed

Chemical name : Oxygen Chemical formula : O<sub>2</sub>

CAS no. : 7782-44-7

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Industrial and professional. Medical use. Balance gas for mixtures.

Calibration gas. Carrier gas. Chemical synthesis. Combustion, melting and cutting processes. Food packaging gas. Laboratory use. Laser gas. Oxidising agent. Process gas. Shielding gas in gas welding. Test gas. Use of

gas to manufacture pharmaceutical products.

It is the responsibility of the end user to ensure that the product as supplied

is suitable for its intended use.

### 1.3 Details of the supplier of the safety data sheet

Supplier name : Linde HKO Limited

Address : 12 Chun Yat Street, Tseung Kwan O Industrial Estate, Tseung Kwan O,

Kowloon, Hong Kong

Phone no. : (852) 2372-2288 Fax no. : (852) 2372-2508

### 1.3 Emergency telephone number

Emergency no. : (852) 2661 0920 (24 hours)



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

### Classification according to Regulation (EC) No 1272/2008

Oxidising gases (Category 1) : H270: May cause or intensify fire; oxidizer.

Gases under pressure (Compressed gas) : H280: Contains gas under pressure; may explode if heated.

### 2.2 Label Elements

Pictograms :



Signal word : Danger

Hazard statements : H270: May cause or intensify fire; oxidiser.

: H280: Contains gas under pressure; may explode if heated.

Precautionary statements

General : None

Prevention : P220: Keep away from clothing and other combustible materials.

: P244: Keep valves and fittings free from oil and grease.

Response : P370+P376: In case of fire: Stop leak if safe to do so.

Storage : P403: Store in a well-ventilated place.

Disposal : None

### 2.3 Other hazards

None



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Chemical name : Oxygen Chemical formula : O<sub>2</sub>

CAS no. : 7782-44-7 EC no. : 231-956-9 INDEX no. : 008-001-00-8

REACH registration number : Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH),

exempted from registration.

Ingredient(s)	CAS No.	EC no.	Purity
Oxygen	7782-44-7	231-956-9	≥99.9%

#### 3.2 Mixtures

Not Applicable

### **SECTION 4: First Aid Measures**

### 4.1 Description of first aid measures

Inhalation : Move the exposed person to fresh air at once.

Eye contact : Adverse effects not expected from this product.

Skin Contact : Adverse effects not expected from this product.

Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2 Most important symptoms and effects, both acute and delayed

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.

### 4.3 Immediate medical attention and special treatment needed

None



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## SECTION 5: Firefighting Measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water. Dry powder. Foam. Carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

Supports combustion and may cause fire/explosion in contact with incompatible substances, strong acids, reducing agents, combustibles and flammables. Materials which burn in air, will burn more vigorously in oxygen enriched atmospheres.

### 5.3 Advice for firefighters

Special fire fighting procedures : In case of fire, stop

: In case of fire, stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain

the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for

firefighters

: Firefighters must use standard protective equipment including flame

retardant coat, helmet with face shield, gloves, rubber boots, and Self-

Contained Breathing Apparatus (SCBA).

### SECTION 6: Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate area. In case of leakage, eliminate all ignition sources. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Monitor the concentration of the released product.

#### 6.2 Environmental Precautions

Prevent further leakage or spillage if safe to do so.

### 6.3 Methods and material for containment and cleaning up

Provide adequate ventilation.

### 6.4 Reference to other sections

See also sections 8 and 13.



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Keep equipment free from oil and grease. Open valve slowly to avoid pressure shock. Use only oxygen approved lubricants and sealants. Use only with equipment cleaned for oxygen service and rated for the pressure. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

### 7.2 Conditions for safe storage, including any incompatibilities

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material. Avoid asphalted locations for storage, transfer and use (ignition risk if spilt). Segregate from flammable gases and other flammable materials being stored.

### 7.3 Specific end uses

None



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

### SECTION 8: Exposure Controls/Personal Protection

### 8.1 Control parameters

Occupational Exposure Limits : No exposure limits have been established for this product.

Biological limits : No biological limits have been established for this product.

### 8.2 Exposure controls

Appropriate engineering controls : Consider a work permit system e.g. for maintenance activities. Ensure

adequate air ventilation. Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when quantities of oxidising gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded

pipes). Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment.

Eye protection : Wear safety glasses.
Hand Protection : Wear leather gloves.
Body protection : Wear safety boots.

Respiratory Protection : Not required under normal conditions of use.



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## **SECTION 9: Physical and Chemical Properties**

### 9.1 Information on basic physical and chemical properties

Appearance

Physical state : Gas

Form : Compressed gas

Colour : Colorless
Odour : Odourless

Odour Threshold : No data available.
pH : No data available.

Melting Point : -218.4 °C Boiling Point : -183 °C

Sublimation Point : No data available.

Critical Temp. (°C) : -118.0 °C

Flash Point : No data available. Evaporation Rate : No data available.

Flammability (solid, gas) : This product is not flammable

Flammability limit - upper (%) : No data available.
Flammability limit - lower (%) : No data available.
Vapour pressure : 4,053 kPa (-124.1 °C)

Vapour density (air=1) :  $1.1 (0 \, ^{\circ}\text{C}) \, \text{AIR}=1$ 

Relative density : 1.1 (0 °C, Reference material: Water)

Solubility (in Water) : 39 mg/l

Partition coefficient (n- : No data available.

octanol/water)

Autoignition Temperature : No data available.

Decomposition Temperature : No data available.

Viscosity

Kinematic viscosityDynamic viscosityExplosive propertiesNo data available.No data available.

Oxidising Properties : Oxidising

#### 9.2 Other information

Additional information : Gas/vapor heavier than air. May accumulate in confined spaces,

particularly at or below ground level.



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## **SECTION 10: Stability and Reactivity**

### 10.1 Reactivity

No reactivity hazard other than the effects described in sub-section below.

### 10.2 Chemical Stability

Stable under normal conditions.

### 10.3 Possibility of Hazardous Reactions

Violently oxidises organic material. May react violently with combustible materials. May react violently with reducing agents.

#### 10.4 Conditions to Avoid

None

### 10.5 Incompatible Materials

Keep equipment free from oil and grease. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (>30 bar) oxygen lines and equipment in case of combustion. May react violently with combustible materials. May react violently with reducing agents.

### 10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## **SECTION 11: Toxicological Information**

### 11.1 Information on toxicological effects

Acute toxicity

Oral : Based on available data, the classification criteria are not met.

Inhalation : Based on available data, the classification criteria are not met.

Dermal : Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation : Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation : Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitisation : Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Reproductive toxicity : Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity

Single Exposure : Based on available data, the classification criteria are not met.

Repeated Exposure : Based on available data, the classification criteria are not met.

Aspiration Hazard : Not applicable to gases and gas mixtures.

## **SECTION 12: Ecological Information**

#### 12.1 Toxicity

No ecological damage caused by this product.

### 12.2 Persistence and Degradability

Not applicable.

#### 12.3 Bioaccumulative Potential

The substance is naturally occurring.

### 12.4 Mobility in Soil

Because of its high volatility, the product is unlikely to cause ground or water pollution.

#### 12.5 Other Adverse Effects

No ecological damage caused by this product.



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

## **SECTION 13: Disposal Considerations**

#### 13.1 Waste treatment methods

Disposal method : Do not discharge into any place where its accumulation could be

dangerous. Cylinders should be returned to the supplier for disposal of

contents.

### **SECTION 14: Transport Information**

### ADR/RID

**14.1 UN Number** : UN 1072

**14.2 UN proper shipping name** : OXYGEN, COMPRESSED

14.3 Transport Hazard Class(es)

Class : 2

Label(s) : 2.2: Non-flammable, non-toxic gases

5.1: Oxidizing substances

Classification Code : 10
Hazard No. : 25
14.4 Packaging group : None

**14.5 Environmental hazards** : Not Applicable

**14.6 Special precautions for user** : None

#### **IMDG**

**14.1 UN Number** : UN 1072

**14.2 UN proper shipping name** : OXYGEN, COMPRESSED

14.3 Transport Hazard Class(es)

**Class** : 2.2

Label(s) : 2.2: Non-flammable, non-toxic gases

: 5.1: Oxidizing substances

**14.4 Packaging group** : None

**14.5 Environmental hazards** : Not Applicable

**14.6 Special precautions for user** : None



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

### IATA

**14.1 UN Number** : UN 1072

**14.2 UN proper shipping name** : OXYGEN, COMPRESSED

14.3 Transport Hazard Class(es)

**Class** : 2.2

Label(s) : 2.2: Non-flammable, non-toxic gases

: 5.1: Oxidizing substances

**14.4 Packaging group** : None

**14.5 Environmental hazards** : Not Applicable

**14.6 Special precautions for user** : None

Other information

Passenger and cargo aircraft : Allowed
Cargo aircraft only : Allowed

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not Applicable

### 14.8 Additional information

Transport precautions : Avoid transport on vehicles where the load space is not separated from the

driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air

ventilation.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Local legislation : Dangerous Goods Ordinance (Chapter 295)



SDS No.: HKO-010G Revision date: 21/10/2022 Version no.: 03

### SECTION 16: Other Information

Other information : Before using this product in any new process or experiment, a thorough

material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this

document, no liability for injury or damage resulting from its use can be

accepted.

Revision date : 21/10/2022

Disclaimer : The above information is believed to be correct. This information should be

used to make an independent determination of the methods to safeguard

workers and the environment.

End of document