

Carrier Hong Kong Limited

安全資料表

1. 產品與用途								
1.1 物料名稱	Blygold PoluAl-XT							
1.2 用途	保耐金化學塗料							
2. 危害成份								
2.1 危害分類及標籤								
	有害	有毒	腐蝕性	易燃	刺激性	爆炸性	助燃	
	()	()	()	(✓)	()	()	()	
2.2 酸鹼值(pH)	無資料			2.3 曝露限制(OEL)	不適用			
2.4 致癌物質	懷疑致癌			2.5 其他危害	無資料			
2.5 潛在危害	中閃點易燃液體，易燃。遇明火、高熱、氧化劑易引燃。							
	吸入、食入、經皮膚接觸均有害，刺激皮膚。							
3. 火警和爆炸資料								
3.1 燃燒物成份比例	無資料		3.2 沸點(°C)	146.4		3.3 溶點(°C)	無資料	
3.4 閃點(°C)	30		3.5 比重	不適用		3.6 氣壓力	不適用	
3.7 爆炸極限(濃度)	不適用		3.8 溶解度	不能在水中溶解		3.9 氣味	溫和	
3.10 滅火設備	建議使用泡沫、二氧化碳、乾粉滅火劑及砂土撲救。							
4. 急救處理								
4.1 眼睛接觸	用大量清水沖洗最少 15 分鐘以上及見醫生							
4.2 皮膚接觸	除去染污衣服。用清水及肥皂清潔。							
4.3 食入	不可引致嘔吐，若持續咳或嘔吐，送院救治。							
4.4 吸入	移到清新空氣地方休息。 保持患者體溫。							
5. 個人防護裝備								
<input checked="" type="checkbox"/> 橡膠手套		<input checked="" type="checkbox"/> 防化學品護眼罩			<input checked="" type="checkbox"/> 口罩			
6. 處理及使用應知事項								
6.1 儲存注意事項	<ul style="list-style-type: none"> • 儲存於陰涼通風庫房、遠離火種、熱源；倉溫不宜超過30℃； • 保持容器密封；與氧化劑、食用化學品分開存放，切忌混儲； • 採用防爆型照明、通風設施； • 禁止使用產生火花的機械設備和工具； • 儲區應務有洩漏應急處理設備和合適的收容材料。 							
6.2 意外洩漏處理的方法	切斷火源。迅速撤離洩漏污染區人員至安全地帶，並進行隔離，嚴格限制出入。盡可能切斷洩漏源。防止進入下水道、排洪溝等限制性空間。							

Carrier Hong Kong Limited

7. 其他資料

- 保持空氣流通
- 不可在工作間吸煙、飲及食。接觸化學品後，必須洗手。

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** POLUAL XT
- **Article number:** 701069 XT-TR
- **UFI:** F110-U0GX-100F-MSN8
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
PROC7 Industrial spraying
PROC10 Roller application or brushing
- **Technical function** Dye
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Blygold International
Hoofdveste 13
3992 DH Houten,
The Netherlands
Telefoon: +31 030 6344344
- **Further information obtainable from:**
Product Safety Department
R&D department
- **1.4 Emergency telephone number:**
NVIC: +31 (0)88 755 8000
Only for the purpose of informing medical personnel in cases of acute intoxications.
Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

Trade name: POLUAL XT

(Contd. of page 1)

Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
.....		
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

Aromatisch polyisocyanat-prepolymeer
o-(p-isocyanatobenzyl)phenyl isocyanate
Solvent naphtha (petroleum), light arom.
4,4'-methylenediphenyl diisocyanate
diphenylmethanediisocyanate, isomeres and homologues
4-isocyanatosulphonyltoluene
2,2'-methylenediphenyl diisocyanate
4-methyl-m-phenylene diisocyanate

· **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

EU

(Contd. on page 3)

Trade name: POLUAL XT

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Resin mixture

Dangerous components:

CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	20-<25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	15-<20%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1	aluminium powder (stabilised) ⚠ Flam. Sol. 1, H228	10-<15%
CAS: 99784-49-3 EC number: 807-385-1	Aromatisch polyisocyanaat-prepolymeer ⚠ Resp. Sens. 1, H334; STOT RE 2, H373; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-<15%
CAS: 37273-56-6	Aromatisch polyisocyanaat-prepolymeer ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	5-<7%
CAS: 5873-54-1 EINECS: 227-534-9 Index number: 615-005-00-9 Reg.nr.: 01-2119480143-45	o-(p-isocyanatobenzyl)phenyl isocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-<7%
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9 Reg.nr.: 01-2119457014-47	4,4'-methylenediphenyl diisocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-<7%
CAS: 4083-64-1 EINECS: 223-810-8 Index number: 615-012-00-7	4-isocyanatosulphonyltoluene ⚠ Resp. Sens. 1, H334; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.5-<1%
CAS: 2536-05-2 EINECS: 219-799-4 Index number: 615-005-00-9 Reg.nr.: 01-2119927323-43	2,2'-methylenediphenyl diisocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1-0.15%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Trade name: POLUAL XT

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** *If symptoms persist consult doctor.*
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:**
No special measures required.
Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
No special measures required.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **7.3 Specific end use(s)** *No further relevant information available.*

EU

(Contd. on page 5)

Trade name: POLUAL XT

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
-------	--

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Fluid

Colour:

According to product specification

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

(Contd. on page 6)

Trade name: POLUAL XT

(Contd. of page 5)

· pH-value:	Mixture is non-polar/aprotic.
· Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 146.4 °C
· Flash point:	30 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	520 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	0.7 Vol % 10.8 Vol %
· Vapour pressure at 20 °C:	5 hPa
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	1.116 g/cm ³ Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic at 20 °C:	Not determined. 27 s (ISO 6 mm)
· Solvent content: Organic solvents: VOC (EC)	45.5 % 45.52 %
· Solids content:	54.5 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Trade name: POLUAL XT

(Contd. of page 6)

· LD/LC50 values relevant for classification:		
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)
CAS: 5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate		
Oral	LD50	2,000 mg/kg (rat)
		mg/kg (rabbit)
Dermal	LD50	9,400 mg/kg (rabbit)
CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral	LD50	2,200 mg/kg (mouse)
Inhalative	LC50/4 h	>15 mg/l (rat)
CAS: 4083-64-1 4-isocyanatosulphonyltoluene		
Oral	LD50	2.234 mg/kg (rat)
CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues		
Inhalative	LC50/4 h	>15 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

Trade name: POLUAL XT


(Contd. of page 7)

- Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR/RID/ADN, ADN, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR/RID/ADN, ADN** 1263 PAINT
- **IMDG, IATA** PAINT
- **14.3 Transport hazard class(es)**
- **ADR/RID/ADN, IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **ADN**
- **ADN/R Class:** 3 Flammable liquids.
- **14.4 Packing group**
- **ADR/RID/ADN, IMDG, IATA** III
- **14.5 Environmental hazards:** Not applicable.
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Hazard identification number (Kemler code):** 30
- **EMS Number:** F-E, S-E
- **Stowage Category** A
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR/RID/ADN**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **Transport category** 3
- **Tunnel restriction code** D/E

(Contd. on page 9)

Trade name: POLUAL XT

(Contd. of page 8)

<ul style="list-style-type: none">· IMDG· Limited quantities (LQ)· Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none">· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Aromatisch polyisocyanat-prepolymeer
o-(p-isocyanatobenzyl)phenyl isocyanate
Solvent naphtha (petroleum), light arom.
4,4'-methylenediphenyl diisocyanate
diphenylmethanediisocyanate, isomeres and homologues
4-isocyanatosulphonyltoluene
2,2'-methylenediphenyl diisocyanate
4-methyl-m-phenylene diisocyanate

- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

(Contd. on page 10)

Trade name: POLUAL XT

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 56a, 56b, 56c, 74
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
- None of the ingredients is listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
- None of the ingredients is listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
- None of the ingredients is listed.
- **Regulation (EC) No 273/2004 on drug precursors**
- None of the ingredients is listed.
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
- None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** product safety department

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Flam. Sol. 1: Flammable solids – Category 1
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity – Category 2

(Contd. on page 11)

Trade name: POLUAL XT

(Contd. of page 10)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
· * **Data compared to the previous version altered.**

—EU—