



## 安全資料表

1. 產品與用途								
1.1 物料名稱		: R32 Refrigerant						
1.2 用途		: 雪種						
2. 危害成份								
2.1 危害分類及標籤								
		有害	有毒	腐蝕性	易燃	刺激性	爆炸性	助燃
		( )	( )	( )	(✓)	( )	( )	( )
2.2 潛在危害		: 火警/爆炸。						
		吸入：大量吸入可能會引致缺氧，呼吸困難。						
		皮膚接觸：液態濺射可能引致凍傷。						
		眼睛接觸：刺激性，液態濺射或霧化噴射可能會引致凍傷。						
3. 火警和爆炸資料								
3.1 燃燒物成份比例		: 無資料	3.2 沸點(°C):		無資料	3.3 溶解度		: 無資料
3.4 閃點(°C)		: 無資料	3.5 比重		: 無資料	3.6 氣味		: 無資料
3.7 滅火設備		: <ul style="list-style-type: none"><li>• 灑水或二氧化碳,化學乾粉之滅火劑，視乎現場燃燒物選擇</li><li>• 防護設備：戴上自給式呼吸器和防護服，防止接觸皮膚和眼睛</li><li>• 著火時釋放有毒煙霧</li></ul>						
4. 急救處理								
4.1 眼睛接觸		: 立即用眼藥水及清水清洗最少 15 分鐘，之後立刻求醫。						
4.2 皮膚接觸		: 立即用清水清洗最少15 分鐘，之後立刻求醫。						
4.3 吸入		: 移至空氣新鮮處，如果沒有呼吸，請進行人工呼吸; 如果呼吸困難，請吸氧氣，之後立刻求醫。						
4.4 食入		: 若清醒時用水漱口，之後立刻求醫。						
5. 個人防護裝備								
<input checked="" type="checkbox"/> 防凍手套			<input checked="" type="checkbox"/> 防化學品護眼罩			<input checked="" type="checkbox"/> 口罩		
6. 處理及使用應知事項								
6.1 儲存注意事項:		: <ul style="list-style-type: none"><li>• 存放於乾爽清涼的地方</li><li>• 保持足夠通風，避免太陽直接照射</li><li>• 遠離熱源、火花和明火。</li><li>• 儲存溫度：不可高於52°C</li></ul>						

6.2 意外洩漏處理的方法:	<ul style="list-style-type: none"> <li>● 在清除洩漏雪種時，穿上個人防護裝備。將洩漏源頭分隔並確保通風正常。</li> <li>● 大量洩漏：要確保地點通風，可用沙、泥及適當物品吸乾。</li> <li>● 關閉所有火源。</li> </ul>
----------------	--

7. 其他資料	
<ul style="list-style-type: none"> <li>- 雪種氣體是重過空氣，如不良通風環境下，雪種會沉底，這時應提供適當之通風或呼吸裝備</li> <li>- 存放及使用位置嚴禁吸煙</li> </ul>	



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
1/17

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name: Difluoromethane (R32)

Other Name: HFC-32

#### Additional identification

Chemical name: Difluoromethane  
Chemical formula: CH<sub>2</sub>F<sub>2</sub>  
INDEX No. -  
CAS-No. 75-10-5  
EC No. 200-839-4  
REACH Registration No. 01-2119471312-47

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.  
Refrigerant.  
Use as an Intermediate (transported, on-site isolated).  
Use for electronic component manufacture.  
Using gas alone or in mixtures for the calibration of analysis equipment.  
Formulation of mixtures with gas in pressure receptacles.

Uses advised against: Consumer use. Contact supplier for more information on uses. Uses other than those listed above are not supported.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Linde Gas GmbH  
Carl-von-Linde-Platz 1  
A-4651 Stadl-Paura

Telephone: +43 50 4273

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number UMC0: +49 89 220 61012 (German), +44 1865 407333 (English)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

#### Physical Hazards



# SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

## Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
2/17

Gases under pressure

Liquefied gas

H280: Contains gas under pressure; may explode if heated.

Flammable gas

Category 1

H220: Extremely flammable gas.

## 2.2 Label Elements



Signal Word:

Danger

Hazard Statement(s):

H220: Extremely flammable gas.  
H280: Contains gas under pressure; may explode if heated.

Precautionary Statements  
General

None.

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381: In case of leakage, eliminate all ignition sources.

Storage:

P403: Store in a well-ventilated place.

Disposal

None.

Supplemental information

EIGA-0783: Contains fluorinated greenhouse gases

## 2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin.

**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Difluoromethane (R32)**

Issue Date: 16.01.2013

Version: 1.2

SDS No.: 000010021734

Last revised date: 11.01.2023

3/17

**SECTION 3: Composition/information on ingredients****3.1 Substances**

Chemical name Difluoromethane  
INDEX No.: -  
CAS-No.: 75-10-5  
EC No.: 200-839-4  
REACH Registration No.: 01-2119471312-47  
Purity: 100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.

Trade name: -

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Difluoromethane	CH <sub>2</sub> F <sub>2</sub>	100%	75-10-5	01-2119471312-47	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

# This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

**SECTION 4: First aid measures**

**General:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**4.1 Description of first aid measures**

**Inhalation:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**Eye contact:** Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
4/17

**Skin Contact:** Contact with evaporating liquid may cause frostbite or freezing of skin. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Get medical attention.

**Ingestion:** Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Hazards:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

## SECTION 5: Firefighting measures

**General Fire Hazards:** Heat may cause the containers to explode.

#### 5.1 Extinguishing media

**Suitable extinguishing media:** Water Spray or Fog. Dry powder. Foam.

**Unsuitable extinguishing media:** Carbon Dioxide.

**5.2 Special hazards arising from the substance or mixture:** No data available.

**Hazardous Combustion Products:** If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Hydrogen fluoride  
; Carbon monoxide  
; Carbonyl difluoride

#### 5.3 Advice for firefighters

**Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
5/17

#### Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

## SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

#### 6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so.

#### 6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition.

#### 6.4 Reference to other sections:

Refer to sections 8 and 13.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
6/17

## SECTION 7: Handling and storage:

### 7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
7/17

**7.2 Conditions for safe storage, including any incompatibilities:**

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

**7.3 Specific end use(s):**

None.

**SECTION 8: Exposure controls/personal protection****8.1 Control Parameters****Occupational Exposure Limits**

None of the components have assigned exposure limits.

**DNEL-Values**

Critical component	Type	Value	Remarks
Difluoromethane	Workers - Inhalation, Systemic, long-term	7035 mg/m <sup>3</sup>	Repeated dose toxicity

**PNEC-Values**

Critical component	Type	Value	Remarks
Difluoromethane	Aquatic (freshwater)	0,142 mg/l	-
Difluoromethane	Sediment (freshwater)	0,534 mg/kg	-

**8.2 Exposure controls****Appropriate engineering controls:**

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
8/17

#### Individual protection measures, such as personal protective equipment

<b>General information:</b>	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.
<b>Eye/face protection:</b>	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
<b>Skin protection</b>	
<b>Hand Protection:</b>	Guideline: EN 388 Protective gloves against mechanical risks. Additional Information: Wear working gloves while handling containers
<b>Body protection:</b>	Wear fire resistant or flame retardant clothing. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.
<b>Other:</b>	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
<b>Respiratory Protection:</b>	When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
<b>Thermal hazards:</b>	No precautionary measures are necessary.
<b>Hygiene measures:</b>	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
<b>Environmental exposure controls:</b>	For waste disposal, see section 13 of the SDS.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
9/17

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless
Odor:	Odorless
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
pH:	Not applicable.
Melting Point:	-136 °C Experimental result, Supporting study
Boiling Point:	-51,6 °C (1.013 hPa) Experimental result, Supporting study
Sublimation Point:	Not applicable.
Critical Temp. (°C):	78,5 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Flammable Gas
Flammability Limit - Upper (%):	33,4 %(V) Experimental result, Supporting study
Flammability Limit - Lower (%):	14 %(V)
Vapor pressure:	17,01 bar (25 °C)
Vapor density (air=1):	1,8
Relative density:	1,1 (Reference material: Water)
Solubility(ies)	
Solubility in Water:	280 g/l
Partition coefficient (n-octanol/water):	0,2
Autoignition Temperature:	530 °C Experimental result, Key study
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.

### 9.2 Other information:

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Molecular weight: 52 g/mol (CH<sub>2</sub>F<sub>2</sub>)



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
10/17

## SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible Materials:	Air and oxidizers. For material compatibility see latest version of ISO-11114.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

General information: May produce irregular heart beat and nervous symptoms.

### 11.1 Information on toxicological effects

Acute toxicity - Oral Product	Based on available data, the classification criteria are not met.
Acute toxicity - Dermal Product	Based on available data, the classification criteria are not met.
Acute toxicity - Inhalation Product	Based on available data, the classification criteria are not met.
Repeated dose toxicity Difluoromethane	NOAEL (Rat(Female, Male), Inhalation, 28 d): 49.500 ppm(m) Inhalation Experimental result, Supporting study
Skin Corrosion/Irritation Product	Based on available data, the classification criteria are not met.
Serious Eye Damage/Eye Irritation Product	Based on available data, the classification criteria are not met.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
11/17

#### Respiratory or Skin Sensitization

**Product** Based on available data, the classification criteria are not met.

#### Germ Cell Mutagenicity

**Product** Based on available data, the classification criteria are not met.

#### Carcinogenicity

**Product** Based on available data, the classification criteria are not met.

#### Reproductive toxicity

**Product** Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity - Single Exposure

**Product** Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity - Repeated Exposure

**Product** Based on available data, the classification criteria are not met.

#### Aspiration Hazard

**Product** Not applicable to gases and gas mixtures..

#### Other Relevant Toxicity Information

Difluoromethane Cardiac sensitisation threshold limit  
>350000 ppm  
Beagle (dog)LOAEC

Cardiac sensitisation threshold limit  
350000 ppm  
Beagle (dog)NOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects.



# SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

## Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
12/17

### SECTION 12: Ecological information

General information: Not applicable

#### 12.1 Toxicity

Acute toxicity  
Product

No ecological damage caused by this product.

Acute toxicity - Fish  
Difluoromethane

LC 50 (Various, 96 h): 1.507 mg/l Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates

Difluoromethane

EC 50 (Daphnid, 48 h): 652 mg/l Remarks: QSAR QSAR, Key study

Chronic Toxicity - Fish

Difluoromethane

NOAEL (Danio rerio; Pimephales promelas): 169 mg/l QSAR QSAR, Supporting study

Toxicity to Aquatic Plants

Difluoromethane

EC 50 (Alga, 96 h): 142 mg/l

#### 12.2 Persistence and Degradability

Product

Not applicable to gases and gas mixtures..

Biodegradation

Difluoromethane

5 % (28 d) Detected in water. Experimental result, Key study

#### 12.3 Bioaccumulative potential

Product

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

#### 12.4 Mobility in soil

Product

Because of its high volatility, the product is unlikely to cause ground or water pollution.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
13/17

#### 12.5 Results of PBT and vPvB assessment

Product Not classified as PBT or vPvB.

#### 12.6 Other adverse effects:

##### Global Warming Potential

Global warming potential: 675

Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and quantities, refer to container label.

Difluoromethane

EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs

- Global warming potential: 675 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1: Hydrofluorocarbons (HFCs) and its mixtures

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### General information:

Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

##### Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

##### European Waste Codes

##### Container:

14 06 01\*: chlorofluorocarbons, HCFC, HFC



# **SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

## **Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
14/17

### **SECTION 14: Transport information**

#### **ADR**

14.1 UN Number: UN 3252  
14.2 UN Proper Shipping Name: DIFLUOROMETHANE  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.1  
Hazard No. (ADR): 23  
Tunnel restriction code: (B/D)  
14.4 Packing Group: -  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: -

#### **RID**

14.1 UN Number: UN 3252  
14.2 UN Proper Shipping Name: DIFLUOROMETHANE  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.1  
14.4 Packing Group: -  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: -

#### **IMDG**

14.1 UN Number: UN 3252  
14.2 UN Proper Shipping Name: DIFLUOROMETHANE  
14.3 Transport Hazard Class(es)  
Class: 2.1  
Label(s): 2.1  
EmS No.: F-D, S-U  
14.4 Packing Group: -  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: -





# SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

## Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
15/17

### IATA

14.1 UN Number: UN 3252  
14.2 Proper Shipping Name: Refrigerant gas R 32  
14.3 Transport Hazard Class(es):  
Class: 2.1  
Label(s): 2.1  
14.4 Packing Group: -  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: -  
Other information  
Passenger and cargo aircraft: Forbidden.  
Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex 1, as amended.:

Classification	Lower-tier Requirements	Upper-tier Requirements
P2. FLAMMABLE GASES	10 t	50 t

### National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 2016/425/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
16/17

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: CSA has been carried out.

## SECTION 16: Other information

Revision Information: Not relevant.

### Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:  
Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).  
European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.  
European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>  
European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.  
International Programme on Chemical Safety (<http://www.inchem.org/>)  
ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.  
Matheson Gas Data Book, 7th Edition.  
National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.  
The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).  
The European Chemical Industry Council (CEFIC) ERICards.  
United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)  
Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).  
Substance specific information from suppliers.  
Details given in this document are believed to be correct at the time of publication.

### Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.

### Training information:

Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 11.01.2023

Version: 1.2

SDS No.: 000010021734  
17/17

#### Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280  
Flam. Gas 1, H220

#### Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. ASHRAE: A2L

#### Last revised date:

11.01.2023

#### Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.